

Chicago Pneumatic CP780 Screwdrivers - Cushion 2.83-4.97NM

High speed & Robust. Fast Screws fastening for better productivity. Reliable & easy-to-adjust cushion Clutch. Ideal tool for general repair, wood, PVC & refurbishing applications. Range: 2.83 - 4.97 Nm 2.06 - 3.7 ft.lbs



Specifications	Details
Handle Type	Pistol <input type="checkbox"/>
Vibration	2.9 m/s ²
Vibration uncertainty (K)	1.4 m/s ²
Sound Power	109.3 db(A)
Average air consumption	Metric: 1.9 l/s 113 l/mn Imperial: 4 cfm
Model Number	CP780
Height	Metric: 150 mm Imperial: 5.9"
Actual air consumption	Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm
Length	Metric: 210 mm Imperial: 8.25"
Product Number	T025095
Brand	Chicago Pneumatic
Max working torque	Metric: 4.97 Nm Imperial: 3.7 ft.lbs
Diameter	Metric: 31 mm Imperial: 0.78"
Air inlet thread size	1/4"

Specifications	Details
Free speed air consumption	Metric: 11.6 l/s Imperial: 25 cfm
Net weight	Metric: 1.13 kg Imperial: 2 1/2 lb
Vibration ISO	ISO-28927-2
Min working torque	Metric: 2.83 Nm Imperial: 2.06 ft.lbs
Sound pressure	98.3 db(A)
Clutch type	Cushion
Bit holder	Quick Change Hexagonal Female
Output drive	1/4"
Free Speed	1800 rpm
Min. Hose Size	Metric: 10 mm Imperial: 3/8"

