

Chicago Pneumatic CP2755 Screwdrivers - Direct drive 7.3NM

High-speed direct drive. Good for soft draw applications. Fast screw rundown. Compact & easy handling



Specifications	Details
Sound Power	101 db(A)
Sound pressure	90 db(A)
Clutch type	Direct drive
Height	Metric: 149 mm Imperial: 5.9"
Max working torque	Metric: 7.3 Nm Imperial: 5.4 ft.lbs
Bit holder	Quick Change Hexagonal Female
Vibration uncertainty (K)	- m/s ²
Vibration	<2.5 m/s ²
Vibration ISO	ISO-28927-2
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Actual air consumption	Metric: 4.7 l/s 283 l/mn Imperial: 10 cfm
Handle Type	Pistol
Diameter	Metric: 21 mm Imperial: 0.83"
Product Number	6151922755
Brand	Chicago Pneumatic

Specifications	Details
Length	Metric: 160 mm Imperial: 6.3"
Model Number	CP2755
Output drive	1/4"
Average air consumption	Metric: 1.2 l/s 71 l/mn Imperial: 2 1/2 cfm
Air inlet thread size	1/4"
Free speed air consumption	Metric: 14 l/s Imperial: 29.7 cfm
Net weight	Metric: 1.03 kg Imperial: 6.3"
Free Speed	2200 rpm

