

Chicago Pneumatic CP781 Screwdrivers - Cushion 6.2-11.3NM

High torque & Robust. Reliable & easy-to-adjust cushion Clutch for powerful fastening. Robust Aluminum body & Steel clutch housing. Ideal tool for general assembly, metal, wood, PVC and refurbishing applications. Range: 6.2 - 11.3 Nm 4.57 - 8.4 ft.lbs



| Specifications | Details |
|------------------------|---|
| Actual air consumption | Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm |
| Brand | Chicago Pneumatic |
| Length | Metric: 226 mm Imperial: 8.88" |
| Model Number | CP781 |
| Output drive | 1/4" |
| Height | Metric: 150 mm Imperial: 5.9" |
| Sound pressure | 99.5 db(A) |
| Clutch type | Cushion |
| Min working torque | Metric: 6.2 Nm Imperial: 4.57 ft.lbs |
| Bit holder | Quick Change Hexagonal Female |
| Product Number | T025096 |
| Sound Power | 110.5 db(A) |
| Air inlet thread size | 1/4" |
| Vibration ISO | ISO-28927-2 |

| Specifications | Details |
|----------------------------|--|
| Average air consumption | Metric: 1.9 l/s 113 l/mn Imperial: 4 cfm |
| Max working torque | Metric: 11.3 Nm Imperial: 8.4 ft.lbs |
| Net weight | Metric: 1.36 kg Imperial: 3 lb |
| Free speed air consumption | Metric: 11.8 l/s Imperial: 25 cfm |
| Vibration uncertainty (K) | - m/s ² |
| Vibration | <2.5 m/s ² |
| Diameter | Metric: 31 mm Imperial: 0.78" |
| Min. Hose Size | Metric: 10 mm Imperial: 3/8" |
| Free Speed | 800 rpm |
| Handle Type | Pistol |

