

Chicago Pneumatic CP782 Screwdrivers - Cushion 3.5-4.97NM

High torque & Robust. Reliable cushion clutch. Comfortable use thanks to low weight. Faster cycle times with 1,800 rpm. Ideal tool for general assembly operations on metal, wood, PVC, or any repair applications. Range: 3.5 - 4.97 Nm 2.58 - 3.7 ft.lbs



Specifications	Details
Min working torque	Metric: 3.5 Nm Imperial: 2.58 ft.lbs
Net weight	Metric: 1.13 kg Imperial: 2 1/2 lb
Max working torque	Metric: 4.97 Nm Imperial: 3.7 ft.lbs
Bit holder	Quick Change Hexagonal Female
Handle Type	Straight
Free speed air consumption	Metric: 7.6 l/s Imperial: 16.1 cfm
Sound Power	104.9 db(A)
Air inlet thread size	1/4"
Clutch type	Cushion
Average air consumption	Metric: 1.9 l/s 113 l/mn Imperial: 4 cfm
Actual air consumption	Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm
Sound pressure	93.9 db(A)
Product Number	T025097
Brand	Chicago Pneumatic

Specifications	Details
Length	Metric: 245 mm Imperial: 9.63"
Model Number	CP782
Output drive	1/4"
Vibration uncertainty (K)	- m/s ²
Vibration	<2.5 m/s ²
Vibration ISO	ISO-28927-2
Min. Hose Size	Metric: 10 mm Imperial: 1/4"
Free Speed	1800 rpm
Diameter	Metric: 30 mm Imperial: 0.76"

