

### Kennedy 115x6x22.23mm A30TBF DPC GRINDING DISC

Type 27 Depressed Center Grinding For use with all portable angle grinders. Not to be used for "free hand" or wet grinding. Optimum angle for use 25 to 35°. Grade A30/AS30 - For general-purpose use on metals. INOX - For use on stainless steel (iron, chlorine and sulphur free). Depressed Centre & Flat Reinforced Cutting & Grinding Discs All Kennedy Depressed Centre and Flat Reinforced Cutting Wheels now carry the "oSa" (The Organisation for the Safety of Abrasives) mark of approval. "oSa" is an association of the world's leading abrasives manufacturers. In France, it is mandatory to use only oSa-certified rough grinding wheels and cutting wheels. Similarly in Germany and Italy, it is strongly recommended that abrasive products conform to the relevant EN standards. "oSa" marked products are guaranteed to meet or exceed the highest worldwide safety standards



Specifications	Details
Special Features	Dedicated for Steel Good Performance Competitively Priced
Additional Conformity	Complies to oSa Regulations Manufactured According to EN12413
Abrasive Material	Aluminium Oxide
Hardness	Very Hard
Thickness	6.0 mm
Series	General Purpose
Grain Size	30-Medium/Coarse
Maximum RPM	13300
Bond Type	Resin Bonded with Fibre Reinforcement
Cutting Application	Sheet Steel
For Use On	Steel

Specifications	Details
Grade Designation	A30T-BF
Type	Type 27
SKU	KEN2301160GTSK
Bore	22 mm
Product Number	3116040
Benefits	High Material Removal rate Long Product Life Manufactured to Assure Operator Safety and Optimum Performance
Diameter	115 mm
Brand	Kennedy
Weight	1

