

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

REED R2005 Infrared Thermometer, 30:1, 1922°F (1050°C), Integrated Type K Thermocouple

This infrared thermometer has a Type K thermocouple input which allows a user to connect probes that measure up to 2498°F (1370°C). Featuring a 30:1 distance to spot ratio, the R2005 has the ability to track maximum, minimum, average and differential readings. It also includes a trigger lock for continuous monitoring, the ability to set high/low audible alarms and store up to 20 datapoints in internal memory.



Specifications	Details
Temp Range	-58 to 1922°F (-50 to 1050°C)
Thermocouple Input	Yes
Laser Class	Class II
Low Battery Indicator	Yes
Weight	10.2oz (290g)
Brand	Reed Instruments
Max/Min	Yes
Display Hold	Yes
Emissivity	0.1 to 1.0 (Adjustable)
Spectral Response	8 to 14μm
Optical Resolution (D:S)	30:1
Operating Humidity Range	10-90%
Storage Temperature	-4 to 140°F (-20 to 60°C)

P.O Box 25898 Sharjah Phone : 06-5436933/06-5436733 E- Mail : gentech@eim.ae United Arab Emirates Fax : 06-5437077 Website : www.generaltech.ae



UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com Tel: +966 (0) 3 834 4264

Fax: +966 3 834 4538

Specifications	Details
Operating Temperature	32 to 122°F (0 to 50°C)
Internal Memory	Yes (20 datapoints)
Auto shut-off	Yes (after 8 secs)
Backlit Display	Yes
Display Size/Type	1.6
Response Time	<1 sec
Dimensions	3.9 x 2.2 x 9.0
Resolution	0.1°F (0.1°C)
Accuracy	(FOR IR THERMOMETER)-58 to -4°F (-50 to -20°C): \pm 9°F(5°C) -4 to 392°F (-20 to 200°C): \pm 1.5% rdg. +3.6°F (2°C) 392 to 1000°F (200 to 538°C): \pm 2.0% rdg. +3.6°F (2°C) 1000 to 1922°F (538 to 1050°C): \pm 3.5% rdg. + 9°F (5°C)

P.O Box 25898 Sharjah United Arab Emirates

Phone : 06-5436933/06-5436733

Fax : 06-5437077

E-Mail:gentech@eim.ae Website: www.generaltech.ae