

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706

## SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

## Control Techniques SP0403-0.75kw, Three Phase, 380-480V AC, Unidrive SP Variable Speed Drive

Unidrive SP is a complete drive automation range that covers the power spectrum from 0.37kW to 1.9MW. All drives share the same flexible control interface regardless of the power rating. Drives are packaged in three formats: Panel Mount, Free-Standing and Modular. In 2018 SP become a legacy product. We can upgrade from SP to M600 or M701 as per the application.



Specifications	Details
Brand	Control Techniques
Supply Phase	3
Max Continuous Current (A)	1.3
Motor Shaft Power (kW)	0.37 kW
Voltage	380 - 480 Vac
Motor Shaft Power (hp)	0.5 hp
Frequency (Hz)	45 - 66 Hz
Output Frequency Range (Hz)	0 - 550Hz
Enclosure	IP21
Dimensions (inch)	12.7 x 2.4 x 8.9
Dimensions (mm)	322 x 62 x 226
Weight lb (Kg)	2.1(4.6)

P.O Box 25898 Sharjah Phone :06-5436933/06-5436733 E-Mail :gentech@eim.ae United Arab Emirates Fax :06-5437077 Website :www.generaltech.ae