



www.lcndt.net

# Portable Digital Densitometer DT-100

USB connect to PC for calibration - New Added

#### Characteristic:

Handy portable type densitometer High Accuracy  $\pm 0.03$  D No warm-up time Program Mode for custom calibration Extremely wide light range of between 650 Cd/m² and 320 000 Cd/m² Light illuminated 4 digit LCD display with low battery indicator Long life due to its low power consumption Rugged design, whole alloy aluminium

Micro USB (Connect to PC For Calibration)



# Portable Digital Densitometer DT-100

## **Technical Specifications:**

Range: 650Cd/m<sup>2</sup>-320 000 Cd/m<sup>2</sup>(5000Lux-1000 000Lux)

Density: 0.00-5.00 D\*

\* We strongly suggest DT-100 work with FV series LED viewers.

Optical Aperture: 3mm diameter Probe Temperature compensated

Display: 4 digit LCD Accuracy: ±0.03 D Resolution: 0.01D Repeatability: 0.02D

Custom calibration range: -0.19 ~ +0.19D (Program Mode)

Detector: Silicon photodiode

Power supply: (AA/1.5V)x2-Alkaline Battery

Battery life: 1200 hours


(Continuous duty, without illuminated)

Dimensions: 160mm x 65mm x 23mm

Weight: 260g


#### Data for reference:

#### PHOTODIODE SPECTRAL RESPONSIVITY



 $\lambda$  -Wavelength -nm

#### PC Utility interface(use USB cable connect with PC):



#### **Standard Components:**

Main unit: 1

Micro USB CABLE(1M): 1

Alkaline Battery: -

Instruction manual (English): 1

Test Report(English): 1

Leather Bag: 1

### **Optional Components:**

AGFA Density Strip, 15-step, certified

You can easily recalibrate your DT-100 with this utility, it fit to any density strips available in market.



#### WenZhou LuCheng NDT Equipment Corp.

Manufacturer of NDT equipments RM.402,NO.189 Yandang Road, 325000 WenZhou, P.R.China.

Tel.:0086-577-86760456 Web:www.Lcndt.net Fax:0086-577-86760456 E-mail:Lendt@163.com

<sup>\*</sup>Support Win7/Win8/Win10 X86/X64 and higher.