


## EVC007

ADOAH043MSS0002H04

Connection technology



### Product characteristics

Socket

For sensors with

M12 connector

Free from silicone

Free from halogen

Gold-plated contacts

### Electrical data

Electrical design		DC PNP
Operating voltage	[V]	10...36 DC
Current rating	[A]	4
Protection class		II

### Environment

Ambient temperature	[°C]	-25...90, cRUUs: max. 75 °C
Ambient temperature (moving)	[°C]	-25...90, cRUUs: max. 75 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

### Tests / approvals

MTTF	[Years]	20027
------	---------	-------

### Mechanical data

Design		angled
Material body		housing: TPU black transparent; sealing: Viton
Material nut		Brass; nickel-plated
Tightening torque for knurled nut [Nm]		0.6...1.5
Drag chain suitability		<p>Bending radius for flexible applications:</p> <p>min. 10 x cable diameter max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s<sup>2</sup></p> <p>Travel speed:</p> <p>Bending cycles:</p> <p>Torsional strain:</p> <p>&gt; 5 million ± 180 °/m</p>
Weight	[kg]	0.079

### Displays / operating elements

Output status indication	LED	2 x yellow
Operation	LED	green

### Electrical connection

Connection		PUR cable / 2 m; 4 x 0.34 mm <sup>2</sup> (42 x Ø 0.1 mm); Ø 4.9 mm; halogen-free
Sheath colour		black



## EVC007



ADOAH043MSS0002H04

Connection technology

### Wiring

Core colours

BK black  
BN brown  
BU blue  
WH white



### Remarks

Pack quantity [piece] 1