

Specifications

Inch

Code No.	Range	Graduation	Accuracy*	Extension rod (optional accessory)
Two-point				
368-021	.08 - .1"	.0001"	±.0001" (range .0001")	—
368-022	.1 - .12"			
368-023	.12 - .16"			
368-024	.16 - .2"			
368-025	.2 - .24"			
368-026	.24 - .28"			
Three-point				
368-261	.275 - .35"	.0001"	±.0001" (range .0001")	952322
368-262	.35 - .425"			
368-263	.425 - .5"			
368-264	.5 - .65"	.0002"	±.00015" (range .00015")	952621
368-265	.65 - .8"			
368-266	.8 - 1"			
368-267	1 - 1.2"			
368-268	1.2 - 1.6"			
368-269	1.6 - 2"			
368-270	2 - 2.5"		±.00025" (range .00025")	952623
368-271	2.5 - 3"			
368-272	3 - 3.5"			
368-273	3.5 - 4"			
368-274	4 - 5"			
368-275	5 - 6"			
368-276	6 - 7"			
368-277	7 - 8"			
368-278	8 - 9"			
368-279	9 - 10"			
368-280	10 - 11"			
368-281	11 - 12"			

* Accuracy specifications apply to the whole length of the measuring pins, and are given both in terms of the limits of deviation of a measurement and the total width of the deviation range (in parentheses).

Dimensions

Unit: mm

Range	a	b	c	L1	L2
2 - 3 mm	—	—	2	12	103.5 - 104
3 - 6 mm	—	—	2.5	22	113 - 114
6 - 12 mm	2 or less	—	2.5	59	102 - 104
12 - 20 mm	0.3 or less	5.6	3.5	82	126 - 130
20 - 30 mm		8.3	5.2	94	137 - 142
30 - 50 mm		13	10	102	145 - 155
50 - 100 mm		17	14	105	150 - 163
100 - 300 mm	12.4 or less	21	13.8	161	227 - 252

Note: External view differs depending on measurement range.