


IE5338

IEBC003BASKG/AS-514

Inductive sensors



Made in Germany



Product characteristics

Inductive sensor	
Metal thread M8 x 1	
Connector	
Operation as 3-wire or 2-wire possible	
Sensing range 3 mm; [f] flush mountable	

Electrical data

Electrical design	3-wire DC PNP; 2-wire DC PNP/NPN
Operating voltage [V]	10...30 DC
Current consumption [mA]	< 10; only in 3-wire operation
Protection class	III
Reverse polarity protection	yes

Outputs

Output function	normally open
Voltage drop [V]	< 2.8
Minimum load current [mA]	2; only in 2-wire operation
Leakage current [mA]	< 0.5
Current rating [mA]	100
Short-circuit protection	pulsed
Overload protection	yes
Switching frequency [Hz]	1000

Range

Sensing range [mm]	3
Operating distance [mm]	0...2.4

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3
Hysteresis [% of Sr]	1...15

Environment

Ambient temperature [°C]	0...60
Protection	IP 67

Tests / approvals

EMC	EN 60947-5-2
MTTF [Years]	2046

Mechanical data

Mounting	flush mountable
Housing materials	Brass white bronze coated; active face: LCP
Weight [kg]	0.019

IE5338

IEBC003BASKG/AS-514

Inductive sensors



Displays / operating elements

Output status indication	LED	yellow (4 x 90°)
--------------------------	-----	------------------

Electrical connection

Connection	M8 connector
------------	--------------

Wiring



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---