


IFS206

IFB3004BAPKG/M/US-104-DPO

Inductive sensors



Made in Germany



Product characteristics

| |
|---|
| Inductive sensor |
| Metal thread M12 x 1 |
| Connector |
| Increased sensing range |
| Gold-plated contacts |
| Sensing range 4 mm; [f] flush mountable |

Electrical data

| | |
|-----------------------------|-------------|
| Electrical design | DC PNP |
| Operating voltage [V] | 10...36 DC |
| Current consumption [mA] | < 10 (24 V) |
| Protection class | II |
| Reverse polarity protection | yes |

Outputs

| | |
|--------------------------|-----------------|
| Output function | Normally closed |
| Voltage drop [V] | < 2.5 |
| Current rating [mA] | 100 |
| Short-circuit protection | pulsed |
| Overload protection | yes |
| Switching frequency [Hz] | 700 |

Range

| | |
|------------------------------|----------|
| Sensing range [mm] | 4 |
| Real sensing range (Sr) [mm] | 4 ± 10 % |
| Operating distance [mm] | 0...3.25 |

Accuracy / deviations

| | |
|------------------------------|--|
| Correction factors | mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.5 / Al approx. 0.4 / Cu approx. 0.3 |
| Hysteresis [% of Sr] | 3...15 |
| Switch-point drift [% of Sr] | -10...10 |

Environment

| | |
|--------------------------|----------|
| Ambient temperature [°C] | -25...70 |
| Protection | IP 67 |

Tests / approvals

| | |
|--------------|---|
| EMC | EN 61000-4-2 ESD: 4 kV CD / 8 kV AD EN 61000-4-3 HF radiated: 10 V/m (80...1000 MHz) EN 61000-4-4 Burst: 2 kV EN 61000-4-6 HF conducted: 10 V (0.15...80 MHz) EN 55011: class B |
| MTTF [Years] | 2017 |

IFS206

IFB3004BAPKG/M/US-104-DPO

Inductive sensors

Mechanical data

| | |
|-------------------|---|
| Mounting | flush mountable |
| Housing materials | Brass white bronze coated; active face: PBT |
| Weight [kg] | 0.026 |


Displays / operating elements

| | | |
|--------------------------|-----|------------------|
| Output status indication | LED | yellow (4 x 90°) |
|--------------------------|-----|------------------|

Electrical connection

| | |
|------------|-------------------------------------|
| Connection | M12 connector; Gold-plated contacts |
|------------|-------------------------------------|

Wiring



Accessories

| | |
|------------------------|-------------|
| Accessories (included) | 2 lock nuts |
|------------------------|-------------|

Remarks

| | | |
|---------------|---------|---|
| Pack quantity | [piece] | 1 |
|---------------|---------|---|