



PROFESSIONAL TORQUE WRENCHES MODELS 650 - 1500 ADJUSTABLE AND 'P' TYPE



For precision applications up to 1,500 N·m

- Exceptionally clear torque signal from unique mechanism
- Non-length dependant so can be used with or without the supplied extension handle (optional on Pro 650)
- Extension handle significantly reduces operator effort to achieve high torque values
- Accurate to ±3% of reading which meets the requirements of ISO 6789-2:2017
- On request 'P' Type wrenches can be set, marked with the setting and certified for production line applications requiring a sealed torque setting. Only if a pre-set has been requested will the tool be supplied with a Declaration of Conformance

2	ADJUSTABLE RATCHET - DUAL SCALE	
14037	Pro 650, 3/4", 130 - 650 N·m, 100 - 480 lbf-ft	
14015	Pro 800, 3/4", 200 - 800 N·m, 150 - 600 lbf-ft	
14016	Pro 800, 1", 200 - 800 N·m, 150 - 600 lbf-ft	
14002	Pro 1000, 3/4", 300 - 1,000 N·m, 220 - 750 lbf-ft	
14003	Pro 1000, 1", 300 - 1,000 N·m, 220 - 750 lbf-ft	
14004	Pro 1500, 3/4", 500 - 1,500 N·m, 370 - 1,100 lbf-ft	
14005	Pro 1500, 1", 500 - 1,500 N·m, 370 - 1,100 lbf-ft	

2	ADJUSTABLE RATCHET - N·m ONLY	
14038	Pro 650, 3/4", 130 - 650 N·m	
14024	Pro 800, 3/4", 200 - 800 N·m	
14025	Pro 800, 1", 200 - 800 N·m	
14026	Pro 1000, 3/4", 300 - 1,000 N·m	
14027	Pro 1000, 1", 300 - 1,000 N·m	
14028	Pro 1500, 3/4", 500 - 1,500 N·m	
14029	Pro 1500, 1", 500 - 1,500 N·m	

2	ADJUSTABLE RATCHET - lbf-ft ONLY	
14044	Pro 650, 3/4", 100 - 480 lbf-ft	
14045	Pro 800, 3/4", 150 - 600 lbf-ft	
14046	Pro 800, 1", 150 - 600 lbf-ft	
14047	Pro 1000, 3/4", 220 - 750 lbf-ft	
14048	Pro 1000, 1", 220 - 750 lbf-ft	
14049	Pro 1500, 3/4", 370 - 1,100 lbf-ft	
14050	Pro 1500, 1", 370 - 1,100 lbf-ft	



2	TORQUE HANDLE ADJUSTABLE - DUAL SCALE	
14040	Pro 650, 22 mm spigot, 130 - 650 N·m, 100 - 480 lbf-ft	



2	FEMALE TORQUE HANDLE ADJUSTABLE - DUAL SCALE	
14041	Pro 650, 14 x 18 mm, 130 - 650 N·m, 100 - 480 lbf-ft	



2	RATCHET PRODUCTION 'P' TYPE (Must be set using a Torque Tester, see pages 80 - 87)	
14039	Pro 650, 3/4", 130 - 650 N·m, 100 - 480 lbf-ft	
14017	Pro 800, 3/4", 200 - 800 N·m, 150 - 600 lbf-ft	
14018	Pro 800, 1", 200 - 800 N·m, 150 - 600 lbf-ft	
14007	Pro 1000, 3/4", 300 - 1,000 N·m, 220 - 750 lbf-ft	
14008	Pro 1000, 1", 300 - 1,000 N·m, 220 - 750 lbf-ft	
14009	Pro 1500, 3/4", 500 - 1,500 N·m, 370 - 1,100 lbf-ft	
14010	Pro 1500, 1", 500 - 1,500 N·m, 370 - 1,100 lbf-ft	
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)	



8	PRO 650 - 1500 ACCESSORY	
14142	Extension Handle (included with Pro 800 - 1500 as standard)	



2	TORQUE HANDLE PRODUCTION 'P' TYPE (Must be set using a Torque Tester, see pages 80 - 87)	
14042	Pro 650, 22 mm spigot, 130 - 650 N·m, 100 - 480 lbf-ft	
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)	



2	FEMALE TORQUE HANDLE PRODUCTION 'P' TYPE (Must be set using a Torque Tester, see pages 80 - 87)	
14043	Pro 650, 14 x 18 mm, 130 - 650 N·m, 100 - 480 lbf-ft	
SQ2222	Pre-set, etch and certify (Allow 3 days delivery for this service)	



All models supplied in carry case