

## EvoTorque 2 ET2-92-4000-230 1"



**Part number:** 180228.B08  
**EAN Bar Code:** 5060207568012  
**NATO number:** -  
**Accuracy:**  $\pm 3\%$   
**Operates between:**  
400.00 - 4000.00 N·m  
295.00 - 3000.00 lbf·ft



### TECHNICAL SPECIFICATIONS

- 1" Square Drive
- 6 rpm
- Tool Weight of 12.85kg
- Calibrated to 20% - 100% of tool's maximum capacity
- Operational targets can be set from 10% of tool capacity
- 230V: 0

### FEATURES

- Each tool is supplied with a traceable calibration certificate
- Torque, Torque & Angle, Torque & Angle with Final Torque or Torque Audit Modes
- 'Usage' counter gives the ability to see the amount of times the tool has been used since the last reset
- "Operation Direction" designed primarily for undoing bolts. When doing sequence tightening, it is now possible to undo an incorrectly tightened bolt without interrupting the sequence
- 2 Stage Tightening gives faster application of a Snug Torque & Angle Target
- "Turn Angle" option can be used to check if bolts have already been tightened in an assembly process
- Allows tool integration into third party control systems
- Maximum Audit Mode target angle increased to 720 degrees
- Ability to produce and store real time graphs via EvoLog
- 2 different lock levels, lock level 1 as per previous lock, lock level 2 will not allow user to exit the run screen or change the target
- For more features please see link to sales leaflet under catalogue below