

TECHNICAL DATA

Features

- Non-invasive measurements, run sensor over surface being tested without scratching or penetrating the surface
- Classifies moisture status as: dry, at risk or wet
- Detects moisture content in various building materials
- Measurement depth from 0.8 to 1.6" (20 to 40mm)
- Data Hold and Min/Max functions
- User adjustable alarms with audible and visual indicators
- Large backlit LCD display
- Low battery indicator and auto shut-off
- Includes batteries

Specifications

Measuring Range:	0 - 100% M.C.
Depth Detection:	0.8 to 1.6" (20 to 40mm)
Resolution:	0.1%
Sensor Type:	Pinless
Display:	LCD Display
Backlit Display:	Yes
Data Hold:	Yes
Min:	Yes
Max:	Yes
Auto Shut-off:	Yes (30 secs)
Low Battery Indicator:	Yes
Power Supply:	3x AAA Batteries
Product Certifications:	CE
Operating Temperature:	32 to 104°F (0 to 40°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity:	0-85%
Dimensions:	9.5 x 2.5 x 1.2" (242 x 63 x 30mm)
Weight:	8oz (226g)



Model	Description
R6010	Pinless Moisture Detector
CA-05A	Soft Carrying Case