KERN OZL 465



The flexible, affordable all-rounder with zoom function for schools, training companies, inspection authorities and laboratories



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Stereo microscope
Product family	OZL-46
Approval	
CE mark	1

Construction

Dimension (W×D×H)	300×240×420 mm
Optical system	Greenough
Tube type	Binocular
Tube angle of inclination	45°
Tube 360° rotation	✓
Eyepieces fixed	\checkmark
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Contrasting methods	Bright field
Interpupillary distance [Max]	75 mm
Interpupillary distance [Min]	55 mm

Ocular

Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	20 mm
Ocular diameter	30 mm

Focussing	
Torque regulation	1
Working distance	105 mm
Zoom [Min]	0,7 x
Zoom [Max]	4,5 x
Magnification ratio	6,4:1
Field of view [Min]	4,4 mm
Field of view [Max]	28,6 mm
Focusing mechanism	coarse drive
Sample height [Max]	140 mm
Standard total magnification [Min]	7 x
Standard total magnification [Max]	45 x
Illumination	
Illumination type incident light	LED
Illumination intensity incident light	3 W
Illumination intensity transmitted	
light	3 W
Illumination type transmitted light	LED
	Reflected light
Illuminance	Transmitted light
	Incident light +
Illumination dimmable	Transmitted light,
	separate
Power Supply	
Input voltage power supply /	100 - 240 V
Input voltage power supply / power [Max]	100 - 240 V
	100 - 240 V 100 - 240 V
power [Max]	
power [Max] Input voltage device / power [Max]	100 - 240 V
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for	100 - 240 V Built-in power supply
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the	100 - 240 V Built-in power supply
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for	100 - 240 V Built-in power supply Power supply unit EURO
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	100 - 240 V Built-in power supply Power supply unit EURO AUS
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 - 240 V Built-in power supply Power supply unit EURO AUS UK
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery	100 - 240 V Built-in power supply Power supply unit EURO AUS
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US CH
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min]	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Environmental conditions Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N)	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Plug-in power supply / adapter for countries - optional Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N) Dimensions packaging (W×D×H)	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C 1 d 445×410×300 mm
power [Max] Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - included with the delivery Plug-in power supply / adapter for countries - optional Countries - optional Storage temperature [Min] Storage temperature [Max] Packing & Shipping Readability force [d] (N)	100 - 240 V Built-in power supply Power supply unit EURO AUS UK US CH -5 °C 40 °C

KERN OZL 465



The flexible, affordable all-rounder with zoom function for schools, training companies, inspection authorities and laboratories

Net weight approx.	4,6 kg
Gross weight approx.	6 kg
Shipping weight	10,9 kg

Pictograms

STANDARD

